

View Online at <https://aerobasegroup.com/nsn/6625-01-308-7985>

Circuit Current For Which Designed:

Dc

Overall Length:

7.039 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.346 inches and 3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.346 inches and 3.406 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Mounting Hole Diameter:

0.250 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 12; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

10.0 volts

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.320 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+400.0 amperes, ac single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Red line 240 amperes

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-16034/1

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0