

View Online at <https://aerobasegroup.com/nsn/6625-01-310-1280>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

7.040 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Overall Height:

4.300 inches

Overall Width:

4.300 inches

Mounting Hole Diameter:

0.310 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and shock resistant and water resistant

Furnished Items And Quantity:

Nut 10; lockwasher 10; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

5.0 volt-amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.190 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+1.0 power factor single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

5 threaded stud

Operating Voltage Rating In Volts:

120.0 ac

Phase:

Three

Special Features:

Calibration at 400 hz; ruggedized

Special Markings:

On front top, lag; lead; on bottom, lead; lag; on back, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with bs 89; complies with ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0