## NSN 6625-01-310-9458

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-310-9458

## Circuit Current For Which Designed:

Ac

## **Dielectric Withstanding Voltage In Volts:**

3000.0

## **Overall Length:**

2.550 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.880 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches

## **Overall Height:**

2.380 inches

## **Overall Width:**

2.380 inches

## Scale Division Quantity:

## 30 single indicator single range

Frequency Rating:

## 60.0 hertz

## Mounting Stud Length:

0.660 inches

## **Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

## Furnished Items And Quantity:

Nut 6; lockwasher 6; seal 1

## Indicator Type:

Dial w/pointer

## Installation Design:

Panel

## Mounting Arrangement Style:

Four hole/stud rectangular/square

## Sensitivity Rating:

0.0025 ohms

## **Dial Scale Marking Color:**

Black single indicator single range

## Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

## Meter Depth Behind Mounting Flange:

1.340 inches

## Meter Body Diameter Behind Mounting Flange:

2.130 inches

- Movement Type:
- Moving iron vane

# NSN 6625-01-310-9458

Ammeter - Page 2 of 2



\//hi+	e single indicator single range
	ter Color:
	k single indicator single range
	er Source:
Exte	
Mou	nting Facility Type And Quantity:
	eaded stud
Scal	e Graduation Type:
	ar single indicator single range
Меа	surement Range:
+0.0	/+15.0 amperes, ac single indicator single range
Mou	nting Stud Diameter:
0.11	2 inches
Scal	e Selection Method:
Tern	ninal
Feat	ures Provided:
Mag	netic shield and zero adjuster
Mov	ement Suspension Method:
Taut	band
Circ	uit Attachment Method And Quantity:
2 thr	eaded stud
Spe	cial Features:
Rug	gedized
Mate	erial:
Plas	tic
Nuc	ear Hardness Critical Feature:
Non	nardened
Surf	ace Treatment:
Pain	t
Styl	e Designator:
Rect	angular flush mtg
Fsc	Application Data:
Test	set, elect. Equip.
She	f Life:
N/a	
Unit	Of Measure:
	ilitarization:
No	