

View Online at <https://aerobasegroup.com/nsn/6625-01-310-9806>

Circuit Current For Which Designed:

Dc

Overall Length:

4.630 inches

Overall Height:

Between 0.470 inches and 0.530 inches

Overall Width:

Between 3.900 inches and 4.100 inches

Mounting Hole Diameter:

Between 0.177 inches and 0.187 inches

Scale Division Quantity:

28 single indicator single range

Distance Between Mounting Facility Centers:

Between 3.552 inches and 3.572 inches

Furnished Items And Quantity:

Nut 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.560 inches

Meter Body Width Behind Mounting Flange:

Between 2.910 inches and 2.970 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Orange single indicator single range

Scale Marking:

7; 6; 5; 4; 3; 2; 1; 0; 1; 2; 3; 4; 5; 6; 7

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

Between 0.470 inches and 0.530 inches

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Features:

Velocity display application

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

5 vdc lamp for illumination

Specification Data:

53711-5267501 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0