

View Online at <https://aerobasegroup.com/nsn/6625-01-311-3550>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

0.6

**Overall Length:**

12.900 inches

**Overall Height:**

4.300 inches

**Overall Width:**

8.000 inches

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**End Application:**

An/alq-172 se

**Furnished Items And Quantity:**

Manual 1, power cord 1, serialized/dated calibration certificate 1, digital voltmeter 1, translator 1, rack adapter 1

**Indicator Type:**

Digital display and dial w/pointer

**Installation Design:**

Rack

**Frequency Response Range:**

+0.000/+11.000 megahertz

**Accuracy In Percent:**

-0.5/+5.0 at full scale single indicator all ranges

**Power Source:**

External

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

3-1/2

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+700.0 volts, ac single indicator 1st range

**Accuracy Rating:**

Porm pct of voltage reading orporm db single indicator all ranges

**Circuit Attachment Method And Quantity:**

1 connector, receptacle

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 240.0 ac

**Interface Compatibility:**

ieee-488

**Special Features:**

10 hz to 20 mhz or 2 hz to 11 mhz; 10, 000 mtbf; 5.44 lb; e/i: an/alq-172, p/n 2487500g001, countermeasures set; voltage ranges: 2 mv, 20 mv, 200 mv, 2 v, 20 v, 200 v, 700 v; 2.5/secondreading rate or 1 second with ac plus dc with damping

**Style Designator:**

D1 rectangular or square

**Supplementary Features:**

Operating temp. Range 0.0 to 50.0deg. C

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0