

View Online at <https://aerobasegroup.com/nsn/6625-01-311-3550>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

0.6

Overall Length:

12.900 inches

Overall Height:

4.300 inches

Overall Width:

8.000 inches

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

End Application:

An/alq-172 se

Furnished Items And Quantity:

Manual 1, power cord 1, serialized/dated calibration certificate 1, digital voltmeter 1, translator 1, rack adapter 1

Indicator Type:

Digital display and dial w/pointer

Installation Design:

Rack

Frequency Response Range:

+0.000/+11.000 megahertz

Accuracy In Percent:

-0.5/+5.0 at full scale single indicator all ranges

Power Source:

External

Display Type:

Light emitting diode

Display Digit Quantity:

3-1/2

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+700.0 volts, ac single indicator 1st range

Accuracy Rating:

Porm pct of voltage reading orporm db single indicator all ranges

Circuit Attachment Method And Quantity:

1 connector, receptacle

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Interface Compatibility:

ieee-488

Special Features:

10 hz to 20 mhz or 2 hz to 11 mhz; 10, 000 mtbf; 5.44 lb; e/i: an/alq-172, p/n 2487500g001, countermeasures set; voltage ranges: 2 mv, 20 mv, 200 mv, 2 v, 20 v, 200 v, 700 v; 2.5/secondreading rate or 1 second with ac plus dc with damping

Style Designator:

D1 rectangular or square

Supplementary Features:

Operating temp. Range 0.0 to 50.0deg. C

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0