

View Online at <https://aerobasegroup.com/nsn/6625-01-311-3596>

Mounting Type:

Rack

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Frequency Range Rating:

+0.000/+2.100 gigahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1

End Application:

An/alq-172, p/n 2487500g001, countermeasures set

Accessory Identifying Number:

H+8642b part no. And option-002 part no. And option-909 part no. And 1494-0059 part no. And 1494-0061 part no.

Output Impedance Rating:

50.0 ohms

Voltage Rating:

Between 100.0 volts and 240.0 volts

Modulation Type:

Am and fm and pulse

Accessory Component Name:

Signal generator; rear panel i/o; front handle and rack flange kit; slide kit; end brackets

Calibrated Signal Output Range:

Minus 140 dbm to plus 20

Functional Description:

Generates signals from 100 khz-2.1 ghz at amplitudes from plus 20 to minus 14 dbm; allows am, fm, pulse and phase modulation of output signal; accuracy porm 1 db; am depth 0-99.9 pct; am bandwidth 100 khz max; fm deviation 3 mhz max; fm bandwidth 20 hz-200 khz; ieee-488 interface; 0-55 deg. C. Operating temp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-j