NSN 6625-01-311-3739

Fault Locating Indicator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-311-3739 Diameter: 0.593 inches Length: 0.765 inches **Current Type:** Dc Dc Voltage Rating: 3.0 volts **Contact Quantity: End Application:** 5895-01-188-0365 coder group **Contact Type:** Wire lead **Presentation Type:** Window **Electrical Connection Quantity:** 2 **Mounting Facility Type And Quantity:** 1 threaded case **Coil Dc Resistance:** Between 106.0 ohms and 274.0 ohms **Features Provided:** Coil and mounting hardware **Case Material:** Aluminum **Special Features:** Two no. 26 awg leads with min lg of 8.0 in. **Supplementary Features:** Wt: 6.5 gm max; pulse power: 50 mw min; pulse lg 25 msec min and 2 usec max **Test Data Document:** 81349-mil-prf-83287 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-83287/4 government specification Shelf Life: N/a **Unit Of Measure:**

Fiig: A532r0

No

Demilitarization:

NSN 6625-01-311-3739

Fault Locating Indicator - Page 2 of 2



Mil-std (military Standard):

Mil-prf-83287 spec.