

View Online at <https://aerobasegroup.com/nsn/6625-01-312-2930>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

1.250 inches

Overall Length:

7.350 inches

Overall Width:

3.410 inches

Environmental Protection:

Dustproof and splash proof

Indicator Type:

Digital display

Installation Design:

Hand held

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator 3rd range

Power Source:

Internal

Display Type:

Light emitting diode

Display Digit Quantity:

4-1/2

Measurement Range:

+0.0/+5.0 nanofarads single indicator 3rd range

Scale Selection Method:

Switch

Features Provided:

Warning feature and electrical overload protection

Criticality Code Justification:

Feat

Accuracy Rating:

Porm 1 pct of reading plus 35 single indicator 3rd range

Special Features:

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts

Style Designator:

Hand-held

Fsc Application Data:

Gpete program

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A310a0