

View Online at <https://aerobasegroup.com/nsn/6625-01-312-6629>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 2.150 inches and 2.160 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.875 inches and 1.885 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.875 inches and 1.885 inches

Overall Height:

Between 2.267 inches and 2.277 inches

Overall Width:

Between 2.985 inches and 2.995 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

Between 0.419 inches and 0.429 inches

Furnished Items And Quantity:

Nut 6; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.295 inches and 1.305 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.120 inches and 2.130 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Mounting Stud Diameter:

Between 0.107 inches and 0.117 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Terminals 0.200 in. Above barrel centerline

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0