

View Online at <https://aerobasegroup.com/nsn/6625-01-314-7439>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2300.0

Overall Length:

7.650 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Overall Height:

4.330 inches

Overall Width:

4.330 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.945 inches

Environmental Protection:

Watertight

Furnished Items And Quantity:

Nut 4; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+55.000/+65.000 hertz

Sensitivity Rating:

120.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.15/+0.15 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

5.220 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

External shunting and magnetic shield and transformer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 screw

Operating Voltage Rating In Volts:

120.0 ac

Special Features:

Red line at 60hz

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Switchboard pwr emer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0