

View Online at <https://aerobasegroup.com/nsn/6625-01-314-7439>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2300.0

**Overall Length:**

7.650 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.380 inches

**Overall Height:**

4.330 inches

**Overall Width:**

4.330 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

0.945 inches

**Environmental Protection:**

Watertight

**Furnished Items And Quantity:**

Nut 4; washer 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+55.000/+65.000 hertz

**Sensitivity Rating:**

120.0 volts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-0.15/+0.15 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

5.220 inches

**Meter Body Diameter Behind Mounting Flange:**

3.970 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+55.0/+65.0 hertz single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Features Provided:**

External shunting and magnetic shield and transformer and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 screw

**Operating Voltage Rating In Volts:**

120.0 ac

**Special Features:**

Red line at 60hz

**Material:**

Stainless steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Switchboard pwr emer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0