

View Online at <https://aerobasegroup.com/nsn/6625-01-314-7784>

Width:

8.250 inches

Length:

11.125 inches

Ac Voltage Rating:

Between 100.0 volts and 240.0 volts

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Major Components:

Probe carriage; detector probe; hband wave guide section; x band wave guide section; x band wave guide to coax adapter; h band to x band wave guidetaper; coaxial slotted line; detector probe

Accessory Component Quantity:

1 and 1 and 4 and 4 and 1 and 1 and 1 and 1

End Application:

T10 meter

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Included

Inclosure Feature:

Multiple item w/housing

Test Type For Which Designed:

Standing wave ratio

Phase:

Single

Special Features:

Amplifier bandwidth 15-130 hz; noise figure 4 db; attenuation 70 db in 10 db steps; bolometer impedance 200 ohms; bolometer current 8.7 ma and 4.7 ma porm 3 pct.; bnc connector; square law calibration; scale ranges: swr 1 to 4; 3.2 to 10; 1 to 1.25 expanded; 0 to 10 db; 0 to 2 db expanded; input impedance: unbiased crystal 20-200 ohms (low range); 2.5 k to 10 kohms (high range)

Height:

7.250 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T228-a