

View Online at <https://aerobasegroup.com/nsn/6625-01-314-7784>

**Width:**

8.250 inches

**Length:**

11.125 inches

**Ac Voltage Rating:**

Between 100.0 volts and 240.0 volts

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Major Components:**

Probe carriage; detector probe; hband wave guide section; x band wave guide section; x band wave guide to coax adapter; h band to x band wave guidetaper; coaxial slotted line; detector probe

**Accessory Component Quantity:**

1 and 1 and 4 and 4 and 1 and 1 and 1 and 1

**End Application:**

T10 meter

**Electrical Power Source Relationship:**

Operating

**Internal Battery Accommodation:**

Included

**Inclosure Feature:**

Multiple item w/housing

**Test Type For Which Designed:**

Standing wave ratio

**Phase:**

Single

**Special Features:**

Amplifier bandwidth 15-130 hz; noise figure 4 db; attenuation 70 db in 10 db steps; bolometer impedance 200 ohms; bolometer current 8.7 ma and 4.7 ma porm 3 pct.; bnc connector; square law calibration; scale ranges: swr 1 to 4; 3.2 to 10; 1 to 1.25 expanded; 0 to 10 db; 0 to 2 db expanded; input impedance: unbiased crystal 20-200 ohms (low range); 2.5 k to 10 kohms (high range)

**Height:**

7.250 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T228-a