NSN 6625-01-315-1327

Pulse Generator - Page 1 of 2



C
View Online at https://aerobasegroup.com/nsn/6625-01-315-1327
Overall Height:
3.500 inches
Overall Width:
8.360 inches
Overall Diameter:
16.600 inches
Operating Tempurature Range:
+0.0/+55.0 degrees celsius
Storage Tempurature Range:
-40.0/+70.0 degrees celsius
End Application:
Lantirn
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic or manual
Control Type:
Local or remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
1 milihertz to 50mhz
Frequency Adjustment Type:
Continuous
Signal Voltage Rating Per Channel:
10.000 volts output and 16.000 volts output
Impedance Rating Per Channel:

50.000 ohms operating channel

Pulse Duration Per Channel:

10.000 nanoseconds operating channel and 999.000 microseconds operating channel

Signal Data Type Per Channel:

Operating channel pulse

Output Wave Shape:

Pulse, variable width and sine and square

Indicator Device Type And Quantity:

1 light and 44 meter

Connection Type And Location:

Connector, plug rear and receptacle, coaxial front

Operating Ac Frequency In Hertz:

48.0 single voltage and 440.0 single voltage

NSN 6625-01-315-1327

Pulse Generator - Page 2 of 2



Calibration Function:

Frequency and pulse duration and pulse repetition

External Ac Operating Voltage In Volts:

100.0 single voltage and 240.0 single voltage

Features Provided:

Internal battery accommodation

Phase:

Single

Supplementary Features:

Used on rf test stand

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200