

View Online at <https://aerobasegroup.com/nsn/6625-01-315-4426>

Circuit Current For Which Designed:

Dc

Overall Length:

2.810 inches

Mounting Hole Diameter:

0.112 inches

Scale Division Quantity:

10 single indicator single range

Overall Diameter:

2.680 inches

Environmental Protection:

Fungus proof and hermetic

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 3

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

11

Accuracy In Percent:

-0.3/+0.3 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.000 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+375.0/+425.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0