## NSN 6625-01-315-4426

**Circuit Current For Which Designed:** 

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-315-4426

Dc
Overall Length:
2.810 inches
Mounting Hole Diameter:
0.112 inches
Scale Division Quantity:
10 single indicator single range
Overall Diameter:
2.680 inches
Environmental Protection:
Fungus proof and hermetic
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 3
Indicator Type:
Vibrating reed
Installation Design:
Panel
Register Quantity:
1
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range
Resonant Reed Quantity:
11
Accuracy In Percent:
-0.3/+0.3 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.000 inches
Meter Body Diameter Behind Mounting Flange:
2.000 inches
Movement Type:
Vibrating reed
Background Color:
White single indicator single range
Power Source:
External

## NSN 6625-01-315-4426

Electrical Frequency Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+375.0/+425.0 hertz single indicator single range
Circuit Attachment Method And Quantity:
2 solder lug
Operating Voltage Rating In Volts:
Between 100.0 ac and 150.0 ac
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A310a0