

View Online at <https://aerobasegroup.com/nsn/6625-01-316-0057>

Overall Length:

16.750 inches

Overall Height:

3.500 inches

Overall Width:

14.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Eip microwave, inc.

Internal Battery Accommodation:

Not included

Specific Usage Design:

Depot rf test stand

Voltage Rating:

Between 100.0 volts and 240.0 volts

Output Frequency Rating:

10.0 megahertz

Unpackaged Unit Weight:

35.000 pounds

Mounting Method:

Rack

Accessory Component Name:

Chassis slides; rack mount kit; transit case; soft pack carrying case; line cord; operating manual

Measurement Type:

Frequency and time

Frequency Range:

+0.000/+18.600 gigahertz

Accuracy Rating:

Pulse porm ge prom de porm aj porm time base error or continuous wave equals time base accuracy porm 1 count

Gate Time:

Between 0.0 microseconds and 1.0 microseconds

Internal Calibration Feature:

Included

Display Type:

Light emitting diode

Display Digit Quantity:

9

Display Units Indicator:

Not included

Display Positioned Decimal Point:

Provided

Display Storage Facility:

Not included

Remote Control Provisions:

Not included

Solid State Feature:

Included

Plug-in Units Provision:

Not included

Standard Frequency Output Feature:

Included

Frequency Accuracy/stability:

Aging: less than 3 times 10 to the 7th per mo; short term: 1 times 10 to the 9th rms for 1 sec averaging time

Output Frequency Waveform:

Square wave

Frequency Output Amplitude:

1.0 volts peak to peak

Phase:

Single

Special Features:

Microwave pulse counter; includesspecial 27 in. Chassis slides for rack, p/n jonanthan 110qd-24-2; type n connector; ieee-488 bus; pulse width 10 ns/9.99 sec

Functional Description:

Provides freq to 1 khz resolution; pulse width to 10 nanosecond resolution

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T297-a