

View Online at <https://aerobasegroup.com/nsn/6625-01-317-3933>

Circuit Current For Which Designed:

Dc

Overall Length:

56.5 millimeters

Scale Division Quantity:

6 single indicator single range

Overall Diameter:

56.0 millimeters

Environmental Protection:

Cold resistant and heat resistant and shock resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Gray single indicator single range and white single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

27.0 millimeters

Meter Body Diameter Behind Mounting Flange:

52.0 millimeters

Background Color:

Black single indicator single range

Pointer Color:

Orange single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 collar

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+20.0/+32.0 volts, dc single indicator single range

Features Provided:

Self-illumination facility and zero adjuster

Circuit Attachment Method And Quantity:

2 connector, plug and 2 solderless lug and 2 wire lead

Special Features:

Sealed bezel

Special Markings:

P and m signs on back of meter; red z on face to indi h or low btry cond

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0