

View Online at <https://aerobasegroup.com/nsn/6625-01-317-6219>

Circuit Current For Which Designed:

Ac

Overall Length:

7.210 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.390 inches

Overall Height:

4.330 inches

Overall Width:

4.330 inches

Mounting Stud Length:

0.620 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 8; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+50.000/+60.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.200 inches

Meter Body Diameter Behind Mounting Flange:

3.940 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Mounting Stud Diameter:

0.250 inches

Features Provided:

Transformer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Request scale and cur xfrm ratio upon order

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0