

View Online at <https://aerobasegroup.com/nsn/6625-01-317-8373>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

350.0

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Indicator Type:

Digital display

Installation Design:

Bench

Frequency Response Range:

+0.000/+12.000 kilohertz

Power Source:

External

Display Type:

Fluorescent tube

Display Digit Quantity:

16

Measurement Range:

+10.0/+1000000000.0 ohms single indicator 5th range

Scale Selection Method:

Switch and terminal

Features Provided:

Autoranging

Accuracy Rating:

2.2ppm 24 hour accuracy single indicator 5th range

Circuit Attachment Method And Quantity:

12 banana plug

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Interface Compatibility:

Ieee-488

Phase:

Single

Functional Classification:

Aa-1.4

Special Features:

External trigger on rear panel; switch selectable for front or rear terminal input; 2 or 4 wire ohm measurements; 5 sampling rate ranges: 100, 000 readings/second at 4.5 digits, 6 readings/second at 8.5 digits

Style Designator:

D1 rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0