

View Online at <https://aerobasegroup.com/nsn/6625-01-317-8373>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

350.0

**Frequency Rating:**

Between 48.0 hertz and 440.0 hertz

**Indicator Type:**

Digital display

**Installation Design:**

Bench

**Frequency Response Range:**

+0.000/+12.000 kilohertz

**Power Source:**

External

**Display Type:**

Fluorescent tube

**Display Digit Quantity:**

16

**Measurement Range:**

+10.0/+1000000000.0 ohms single indicator 5th range

**Scale Selection Method:**

Switch and terminal

**Features Provided:**

Autoranging

**Accuracy Rating:**

2.2ppm 24 hour accuracy single indicator 5th range

**Circuit Attachment Method And Quantity:**

12 banana plug

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 240.0 ac

**Interface Compatibility:**

Ieee-488

**Phase:**

Single

**Functional Classification:**

Aa-1.4

**Special Features:**

External trigger on rear panel; switch selectable for front or rear terminal input; 2 or 4 wire ohm measurements; 5 sampling rate ranges: 100,000 readings/second at 4.5 digits, 6 readings/second at 8.5 digits

**Style Designator:**

D1 rectangular or square

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0