

View Online at <https://aerobasegroup.com/nsn/6625-01-318-5667>

Overall Length:

19.900 inches

Overall Height:

5.900 inches

Overall Width:

12.200 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

End Application:

F110ge100 eng serd 5042

Accessory Components And Quantity:

Probe 2; scale lamp 1; fuse 1; instruction manual 1

Voltage Rating:

Between 100.0 volts and 240.0 volts

Beam Quantity:

4

Screen Size:

7 in. Square

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Single Trigger Sweep Duration:

Between 0.0 seconds and 50.0 seconds

Trigger Sweep Polarity Switch:

Not included

Trigger Sweep Marker Intervals:

5 nanosec to 50 millisecc per div

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Input Intensity Modulation Feature:

Not provided

Frequency Response Rating:

Provided

Calibrated Screen Scale:

Included

Trace Storage Tube:

Included

Viewing Screen Voltage Rating:

20.0 kilovolts

Plug In Unit Function And Quantity:

Expansion memory 1

Camera Recording Device Accommodation:

Not provided

Special Features:

Digital; 100 mhz sampling clock; 10k word memory; dc-35 mhz storage; gp-ib interface (external control); 10 programs of 100 steps; x-y recorder; 4 waveform display; measurements: low-level signal noises and waveform distortions; opt 1 is expansion memory (vq-051p40); 8x10 div crt; deflection factors: vertical: 5mv to 5v/div, in 1-2-5 sequence; x-y: 5 mv to 5v/div.; time base: 50 ns to 50 sec/div sweep time; calibrator 0.3v, 1 khz positive-going square wave; bandwidth: crt: dc-100 mhz non-storage, storage: dc-35 mhz; x-y: dc-35 mhz bandwidth; dual-trace; data displayed as dots, with linear interpolation, or with sine interpolation

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g