

View Online at <https://aerobasegroup.com/nsn/6625-01-319-0148>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

4.094 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

4.500 inches

Overall Width:

4.500 inches

Frequency Rating:

400.0 hertz

Mounting Stud Length:

0.625 inches

Environmental Protection:

Watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

+0.0/+0.1 at 1/2 scale single indicator single range

Meter Depth Behind Mounting Flange:

2.812 inches

Meter Body Diameter Behind Mounting Flange:

3.930 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+430.0/+470.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Rectifier circuit and transformer

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0