

View Online at <https://aerobasegroup.com/nsn/6625-01-319-0149>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 3.720 inches and 3.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.795 inches and 3.815 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.782 inches and 0.798 inches

Overall Height:

1.506 inches

Overall Width:

Between 1.897 inches and 1.907 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

20 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 2.524 inches and 2.584 inches

Meter Body Width Behind Mounting Flange:

Between 3.400 inches and 3.460 inches

Scale Marking:

Zero to 20

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

1 connector, receptacle

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Panel, trim system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0