

View Online at <https://aerobasegroup.com/nsn/6625-01-319-0485>

Width:

7.000 inches

Length:

11.000 inches

Ac Voltage Rating:

Between 95.0 volts and 132.0 volts

Dc Voltage Rating:

5.0 volts and 28.0 volts

Frequency Rating:

Between 47.0 hertz and 440.0 hertz

Major Components:

Instrument subassy housing; carrying case; w1 monitor cable assembly; w2 hud cable assembly; w3 power cable assembly; w4 triax cable assembly

Accessory Component Quantity:

6

End Application:

Field level test of vsdu ip-1571/asn, computer monitor ip-149 (v)i/u, tv monitor ip-1504(v) i/u, high resolution video monitor

Accessory Controlling Agency:

Systems research laboratories

Accessory Identifying Number:

2748-0303-1 part no. And ay1fa29h16 part no. And 2748-0306-1 part no. And 2748-0304-1 part no. And 2748-0305-1 part no. And 2748-307-1 part no.

Joint Electronics Type Designation System Item Type Number:

Ts-4390/g

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Not included

Inclosure Feature:

Multiple item w/carrying case

Test Type For Which Designed:

Alignment

Operating Test Capability:

Temperature 0 - 25 degrees celcius; altitude 0 - 15, 000 ft

Phase:

Single

Special Features:

Noun: test set, video; video output levels: rs-343a, rs-170a, stanag 3350 (into 75 ohm); signal levels: video 0.714 v p-p & sync 0.286 v p-p; horizontal scan: 26, 250 hz at 875 lines, 15, 626 hz at 825 lines, 15, 750 hz at 525 lines; dot clock: 16.382 mhz at 875 line rate, 8.191 mhz at 525 & 625 line rates

Height:

9.500 inches

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fig:

T228-a