

View Online at <https://aerobasegroup.com/nsn/6625-01-320-5542>

Current Type:

Ac

Accessory Components And Quantity:

Bnc connector 1

Voltage Rating:

250.0 volts

Beam Quantity:

1

Graduation Interval:

Horizontal 25 div with 1 div equals 20 horizontal dots or 20 samples, vertical equals 20 div with 10 pixels/div

Sweep Circuits:

Not included

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Not provided

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Special Features:

Digital, 20 mhz; 2 channel, 8 bit, with 128k buffer per channel; ac/dc coupling, selectable gain from 10 mv/div to 50v/div, analog trigger, metal case; self-contained linear power supply; bandwidth: dc - dc to 10 mhz, ac - 10 hz to 10 mhz; memory 64, 588 8-bit bytes per channel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g