

View Online at <https://aerobasegroup.com/nsn/6625-01-320-7718>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.306 inches and 1.318 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.306 inches and 1.318 inches

Overall Height:

Between 1.734 inches and 1.766 inches

Overall Width:

Between 1.734 inches and 1.766 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+0.025/+30000.000 kilohertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-4.0/+4.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+150.0 volts, rf single indicator single range

Features Provided:

Luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Test set, elect. Equip.

Special Markings:

Green band from 100 to 130 v

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Special Test Features:

Conforms to mil-m-10304/3, type mr13a150arvvr

Style Designator:

Rectangular flush mtg

Supplementary Features:

Ruggedized

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0