

View Online at <https://aerobasegroup.com/nsn/6625-01-320-8742>

Circuit Current For Which Designed:

Ac

Overall Length:

18.200 inches

Overall Height:

5.750 inches

Overall Width:

16.800 inches

Frequency Rating:

Between 48.0 hertz and 66.0 hertz

Indicator Type:

Digital display

Installation Design:

Rack

Frequency Response Range:

+10.000 to 1600.000 megahertz

Power Source:

External

Measurement Range:

+0.0 to 30.0 decibels single indicator single range

Accuracy Rating:

Porm 0.1 db single indicator single range

Circuit Attachment Method And Quantity:

1 connector, receptacle

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Phase:

Single

Special Features:

C/o front panel handle kit, rack mtg flange kit, ears, slide; gain minus 20-plus 40 db; hp-ib compatible; stores 4 noise source enr tables; displays freq up to 99.999 ghz; 34 lbs; connectors: rf input: (f), noise source drive: bnc(f) ; 50 ohm impedance; maximum operating input power: minus 10 dbm; noise source drive: 28 porm 0.1v; mtbf 18, 000 hours

Style Designator:

D1 rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0