

View Online at <https://aerobasegroup.com/nsn/6625-01-321-5063>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

3.093 inches

Mounting Hole Diameter:

0.150 inches

Frequency Rating:

60.0 hertz

Overall Diameter:

3.500 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 7; lockwasher 5; seal 1

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

2

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+55.000/+65.000 hertz

Sensitivity Rating:

150.0 volts

Resonant Reed Quantity:

11

Meter Depth Behind Mounting Flange:

2.312 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Phase:

Single

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with asa standard

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0