

View Online at <https://aerobasegroup.com/nsn/6625-01-321-5063>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

3.093 inches

**Mounting Hole Diameter:**

0.150 inches

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Nut 7; lockwasher 5; seal 1

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

2

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+55.000/+65.000 hertz

**Sensitivity Rating:**

150.0 volts

**Resonant Reed Quantity:**

11

**Meter Depth Behind Mounting Flange:**

2.312 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Measurement Range:**

+55.0/+65.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 150.0 ac

**Phase:**

Single

**Special Features:**

Ruggedized

**Special Markings:**

On back, sealed do not open

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Complies with asa standard

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0