

View Online at <https://aerobasegroup.com/nsn/6625-01-321-7473>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

2.000 inches

Overall Height:

0.730 inches

Overall Width:

2.310 inches

Mounting Hole Diameter:

0.136 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Dustproof

Distance Between Mounting Facility Centers:

Between 1.995 inches and 2.005 inches

Barrel Width:

0.935 inches

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.475 inches

Meter Body Width Behind Mounting Flange:

1.750 inches

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bezel and 2 screw and 2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+25.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.235 inches

Meter Barrel Depth:

0.935 inches

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Edgewise meter

Material:

Plastic acrylic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Supplementary Features:

1000 ohms per v res

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0