

View Online at <https://aerobasegroup.com/nsn/6625-01-322-6659>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2300.0

Overall Length:

5.710 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Overall Height:

4.330 inches

Overall Width:

4.330 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.625 inches

Environmental Protection:

Dust resistant and water resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

20.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.790 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Psig; 0 to 30

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Electrical overload protection

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Suppressed zero 4 ma sensitivity

Material:

Plastic polycarbonate

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Self contained

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0