

View Online at <https://aerobasegroup.com/nsn/6625-01-322-9508>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

5.230 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.380 inches

**Overall Height:**

4.500 inches

**Overall Width:**

4.500 inches

**Mounting Hole Diameter:**

0.310 inches

**Scale Division Quantity:**

120 single indicator single range

**Frequency Rating:**

55.0 hertz

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 7; lockwasher 7; seal 1; transformer 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+40.000/+70.000 hertz

**Sensitivity Rating:**

5.0 amperes

**Dial Scale Marking Color:**

Black single indicator single range and red single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.380 inches

**Meter Body Diameter Behind Mounting Flange:**

3.970 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+1200.0 amperes, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Self-illumination facility and transformer and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

3 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Red lin a 960 amperes

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Complies with ansi c39.1

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0