

View Online at <https://aerobasegroup.com/nsn/6625-01-324-4418>

Circuit Current For Which Designed:

Ac and dc

Overall Length:

11.000 inches

Overall Height:

7.000 inches

Overall Width:

10.000 inches

Scale Division Quantity:

30 single indicator all ranges

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Indicator Type:

Dial w/pointer

Installation Design:

Hand held

Frequency Response Range:

+0.000/+1.000 megahertz

Dial Scale Marking Color:

Black single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External and internal

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+4.0/+450.0 megahertz single indicator 2nd range

Features Provided:

Internal battery accommodation and portable

Movement Suspension Method:

Taut band

Operating Voltage Rating In Volts:

Between 110.0 ac and 200.0 ac

Phase:

Single

Special Features:

Up to 13 channels; case w/lid and storage section for ac cord, jumpers, connectors, testing handbook, instruction manual, shoulder strap, carrying case; 5-100 v ac-dc measurement range; 0-120 f.; accuracy: freq - porm 1 mhz, amplitude - porm 0.5 db room temp, and porm 1.0 over temp when calibrated at that temp; internal nicad batteries; 11 lbs.

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0