

View Online at <https://aerobasegroup.com/nsn/6625-01-324-4418>

**Circuit Current For Which Designed:**

Ac and dc

**Overall Length:**

11.000 inches

**Overall Height:**

7.000 inches

**Overall Width:**

10.000 inches

**Scale Division Quantity:**

30 single indicator all ranges

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Hand held

**Frequency Response Range:**

+0.000/+1.000 megahertz

**Dial Scale Marking Color:**

Black single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External and internal

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+4.0/+450.0 megahertz single indicator 2nd range

**Features Provided:**

Internal battery accommodation and portable

**Movement Suspension Method:**

Taut band

**Operating Voltage Rating In Volts:**

Between 110.0 ac and 200.0 ac

**Phase:**

Single

**Special Features:**

Up to 13 channels; case w/lid and storage section for ac cord, jumpers, connectors, testing handbook, instruction manual, shoulder strap, carrying case; 5-100 v ac-dc measurement range; 0-120 f.; accuracy: freq - porm 1 mhz, amplitude - porm 0.5 db room temp, and porm 1.0 over temp when calibrated at that temp; internal nicad batteries; 11 lbs.

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular or square

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0