NSN 6625-01-325-0477

Ammeter - Page 1 of 2

Dc

Overall Length: 2.240 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-325-0477

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 1.880 inches |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.880 inches |
| Overall Height: |
| 2.470 inches |
| Overall Width: |
| 2.470 inches |
| Scale Division Quantity: |
| 40 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| End Application: |
| 6130-01-164-0548 power supply |
| Furnished Items And Quantity: |
| Nut 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range and red single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.060 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.170 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| |

NSN 6625-01-325-0477

Ammeter - Page 2 of 2



| Power Source: |
|---|
| External |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+8.0 amperes, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.112 inches |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ruggedized |
| Special Markings: |
| 6 to 8 amp dc red band |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |