

View Online at <https://aerobasegroup.com/nsn/6625-01-325-0477>

Circuit Current For Which Designed:

Dc

Overall Length:

2.240 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches

Overall Height:

2.470 inches

Overall Width:

2.470 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Shock resistant and vibration resistant

End Application:

6130-01-164-0548 power supply

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.060 inches

Meter Body Diameter Behind Mounting Flange:

2.170 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+8.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

6 to 8 amp dc red band

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0