

View Online at <https://aerobasegroup.com/nsn/6625-01-327-5026>

**Overall Length:**

4.800 inches

**Overall Height:**

1.500 inches

**Overall Width:**

3.700 inches

**Environmental Protection:**

Moisture proof

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Average Life Measurement:**

Not rated

**Basic Shape Style:**

Rectangular or square

**Inclosure Type:**

Encased

**Installation Design:**

Free-standing

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

0.0 kilohertz operating channel and 200.0 kilohertz operating channel

**Signal Voltage Rating Per Channel:**

1.000 millivolts output

**Impedance Rating Per Channel:**

50.000 ohms operating channel

**Signal Data Type Per Channel:**

Operating channel digital

**External Dc Operating Voltage In Volts:**

9.0 single voltage

**Special Features:**

C/o carrying case, 2 alkaline batteries, plug-in power supply, male/female bnc adaptor, instruction/service manual; maximum output voltage 0.5

**Functional Description:**

Converts input optical power signals from led's, lasers and fiber optic cable into electrical output signals; applications: waveforms in optical fibers, led rise/decay time, laser waveforms, optical fiber dispersion, fiber loss (pulsed)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A32200