

View Online at <https://aerobasegroup.com/nsn/6625-01-327-5026>

Overall Length:

4.800 inches

Overall Height:

1.500 inches

Overall Width:

3.700 inches

Environmental Protection:

Moisture proof

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Installation Design:

Free-standing

Circuit Construction Type:

Solid state

Frequency Per Channel:

0.0 kilohertz operating channel and 200.0 kilohertz operating channel

Signal Voltage Rating Per Channel:

1.000 millivolts output

Impedance Rating Per Channel:

50.000 ohms operating channel

Signal Data Type Per Channel:

Operating channel digital

External Dc Operating Voltage In Volts:

9.0 single voltage

Special Features:

C/o carrying case, 2 alkaline batteries, plug-in power supply, male/female bnc adaptor, instruction/service manual; maximum output voltage 0.5

Functional Description:

Converts input optical power signals from led's, lasers and fiber optic cable into electrical output signals; applications: waveforms in optical fibers, led rise/decay time, laser waveforms, optical fiber dispersion, fiber loss (pulsed)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32200