

View Online at <https://aerobasegroup.com/nsn/6625-01-329-4423>

Circuit Current For Which Designed:

Dc

Overall Length:

4.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.879 inches

Overall Height:

2.375 inches

Overall Width:

2.375 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

50 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.500 inches

Meter Body Diameter Behind Mounting Flange:

2.062 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

Percent battery energy; 0 to 100

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Circuit Attachment Method And Quantity:

2 threaded stud and 2 wire lead

Operating Voltage Rating In Volts:

24.0 dc

Special Features:

100 pct indication equals 2.08 v/cell

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0