

View Online at <https://aerobasegroup.com/nsn/6625-01-329-8718>

Circuit Current For Which Designed:

Ac

Overall Length:

5.219 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.313 inches

Overall Width:

4.313 inches

Frequency Rating:

Between 40.0 hertz and 70.0 hertz

Mounting Stud Length:

0.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 10; washer 10

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.375 inches

Meter Body Diameter Behind Mounting Flange:

3.969 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+1500.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

All windings 5 amperes

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0