

View Online at <https://aerobasegroup.com/nsn/6625-01-329-8720>

Circuit Current For Which Designed:

Ac

Overall Length:

7.031 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.313 inches

Overall Width:

4.313 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Mounting Stud Length:

0.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 10; washer 10

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.188 inches

Meter Body Diameter Behind Mounting Flange:

3.969 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+5000.0 kilowatts single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

Integral solid state transducers

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0