

View Online at <https://aerobasegroup.com/nsn/6625-01-330-2744>

Inclosure Feature:

Single item w/housing

Test Type For Which Designed:

Fault isolate mobile telephone base station

Special Features:

Receiver measurement: test signal signal generator freq range 0.4-520 mhz, output - cw/fm minus 137-plus 13dbm, am - minus 137-plus 7 dbm; output impedance 50 ohms vswr porm 1.2; af synthesizer/selective call encoder: freq range - 10 hz-25 khz; output voltage: 0.1 mv-5 v; amplitude modulation: freq: 50 hz-20 khz internal, 50 hz-5khz external; freq modulation: 20 hz-20 khz; internal voltage (rms) at fm ext 1v porm 1 pct; phase modulation: freq 100 hz to 6 khz; af freq meter, af level meter, distortion meter, sinad-ratio meter, s/n meter, rf freq meter, power meter, freq deviation meter, phase deviation meter, modulation depth meter, dc voltmeter, dc ammeter; manual, automatic; self-contained; iec-bus compatible; 7 fixed freq; non-volatile memory; crystal oscillator; digital display: 6 lcd quasi-analog

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T228-a