

View Online at <https://aerobasegroup.com/nsn/6625-01-332-6662>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 5.620 inches and 5.640 inches

Overall Height:

Between 1.880 inches and 1.900 inches

Overall Width:

Between 3.770 inches and 3.790 inches

Indicator Type:

Digital display

Installation Design:

Panel

Frequency Response Range:

+47.000/+63.000 hertz

Sensitivity Rating:

10.0 millivolts

Meter Depth Behind Mounting Flange:

Between 5.310 inches and 5.330 inches

Meter Body Width Behind Mounting Flange:

3.380 inches

Background Color:

Black single indicator single range

Mounting Facility Type And Quantity:

2 snap slide

Display Type:

Light emitting diode

Display Digit Quantity:

3-1/2

Measurement Range:

-19.99/+19.99 volts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

Between 1.760 inches and 1.780 inches

Features Provided:

Electrical overload protection

Accuracy Rating:

Porm 0.05 pct of reading porm 1.5 counts single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

2 clip and 6 screw

Special Features:

0 to 4 per second read rate

Material:

Plastic polycarbonate

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Specification Data:

54933-104337 manufacturers specification control

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0