NSN 6625-01-337-5308

Field Strength Meter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-337-5308

Circuit Current For Which Designed: Ac Frequency Rating: 60.0 hertz Installation Design: Bench Operating Voltage Rating In Volts: 120.0 ac Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disat least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plattmer with a stop level and reset (stop level selectable at 50, 100 or 500 volts for both polarities); recorder output: 0 to 15 voltage measurement:	5 5 .
Frequency Rating: 60.0 hertz Installation Design: Bench Operating Voltage Rating In Volts: 120.0 ac Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disat least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Installation Design: Bench Operating Voltage Rating In Volts: 120.0 ac Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self dist at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Installation Design: Bench Operating Voltage Rating In Volts: 120.0 ac Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disc at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Departing Voltage Rating In Volts: 120.0 ac Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disated teast 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Operating Voltage Rating In Volts: 120.0 ac Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disc at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disc at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Special Features: Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disc at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: plate	5 5 .
Portable charged plate air ionization monitor with hard protective case and mounting tripod; charged plate: isolated self disc at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization lev ions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: pla	5 5 .
at least 15 pico farads which will discharge less than 10% in 5 minutes with 40% relative humidity and ambient ionization levions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: pla	5 5 .
ions/cc; power supplies for each polarity (+, -); voltage measurement: noncontacting electrostatic fieldmeter; displays: pla	els less than 200
timer with a stop level and reset (stop level selectable at 50, 100 or 500 volts for both polarities); recorder output: 0 to 15 v	ate voltage (+, -),
	using bnc
connection	
Functional Description:	
Used to monitor effectiveness of air ionization system in esd sensitive areas	
Supplementary Features:	
Manufacturers name: monitor, plate charge	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A310a0	