

View Online at <https://aerobasegroup.com/nsn/6625-01-338-8911>

Overall Length:

16.750 inches

Wattage Rating In Watts:

130.0

Overall Height:

5.250 inches

Overall Width:

13.500 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 66.0 hertz

End Application:

Dits

Internal Battery Accommodation:

Not included

Voltage Rating:

Between 100.0 volts and 240.0 volts

Electrical Connection Quantity:

3

Unpackaged Unit Weight:

19.500 pounds

Measurement Type:

Frequency and ratio and time

Frequency Range:

+0.000/+1.300 gigahertz

Accuracy Rating:

Porm 20 mv, porm 5 pct reading

Gate Time:

Between 0.1 seconds and 4.0 seconds

Sensitivity Rating:

20mv rms sinewave

Ratio Display:

Offset, normalize, and scale measure functions

Internal Calibration Feature:

Included

Display Type:

Light emitting diode

Display Digit Quantity:

12

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Display Storage Facility:

Included

Remote Control Provisions:

Included

Solid State Feature:

Included

Inclosure Material And Location:

Aluminum body

Plug-in Units Provision:

Not included

Standard Frequency Output Feature:

Not included

Phase:

Single

Special Features:

16 front panel measurement functions; opt 040: 4 phantom functions; opt 030: c channel 150 mhz to 1.3 ghz; opt 908: rack flange kit

Functional Description:

Built-in rise time, duty cycle, pulse width, slew rate, phase measure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T297-a