

View Online at <https://aerobasegroup.com/nsn/6625-01-340-6009>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.500 inches

Overall Diameter:

2.050 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and vibration resistant

Furnished Items And Quantity:

Nut 12; washer 18; clip, shorting 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.1 milliamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.330 inches and 1.670 inches

Meter Body Diameter Behind Mounting Flange:

1.940 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

0 to 2 lwc g/m cubed

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Warning feature and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

6 threaded stud

Special Features:

Fail flag marked fail in de-energized position; black in energized position

Special Markings:

White band w/t from 0 to 0.25; white and yellow band w/l from 0.25 to 0.5; yellow band w/m from 0.5 to 1.0; red band w/h from 1.0 to 2.0

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

1 ko int res

Specification Data:

59885-00512-0239 manufacturers source control

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0