

View Online at <https://aerobasegroup.com/nsn/6625-01-341-9674>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

1.938 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Mounting Stud Length:

0.375 inches

Distance Between Mounting Facility Centers:

2.783 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.625 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+35.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.190 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

At pos term.

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Zinc

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0