

View Online at <https://aerobasegroup.com/nsn/6625-01-342-8935>

Circuit Current For Which Designed:

Ac or dc

Overall Depth:

1.300 inches

Overall Length:

3.500 inches

Overall Width:

2.400 inches

Scale Division Quantity:

50 single indicator 2nd range 50 single indicator 3rd range 50 single indicator 4th range 50 single indicator 6th range 50 single indicator 7th range 50 single indicator 8th range 50 single indicator 9th range 50 single indicator 10th range 50 single indicator 11th range 50 single indicator 12th range 50 single indicator 13th range

End Application:

2510-01-327-4170 battle damage kit, m

Furnished Items And Quantity:

Fuse 1

Indicator Type:

Dial w/pointer

Installation Design:

Hand held

Sensitivity Rating:

2000.0 ohms per volt

Dial Scale Marking Color:

Red single indicator 1st range black single indicator 2nd range black single indicator 3rd range black single indicator 4th range black single indicator 5th range black single indicator 6th range black single indicator 7th range black single indicator 8th range black single indicator 9th range black single indicator 10th range black single indicator 11th range black single indicator 12th range black single indicator 13th range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator 1st range -4.0/+4.0 at full scale single indicator 2nd range -4.0/+4.0 at full scale single indicator 3rd range -4.0/+4.0 at full scale single indicator 4th range -4.0/+4.0 at full scale single indicator 5th range -5.0/+5.0 at full scale single indicator 6th range -5.0/+5.0 at full scale single indicator 7th range -5.0/+5.0 at full scale single indicator 8th range -5.0/+5.0 at full scale single indicator 9th range -4.0/+4.0 at full scale single indicator 10th range -4.0/+4.0 at full scale single indicator 11th range -4.0/+4.0 at full scale single indicator 12th range -4.0/+4.0 at full scale single indicator 13th range

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External or internal

Scale Graduation Type:

Nonlinear single indicator 1st range linear single indicator 2nd range linear single indicator 3rd range linear single indicator 4th range nonlinear single indicator 5th range linear single indicator 6th range linear single indicator 7th range linear single indicator 8th range linear single indicator 9th range linear single indicator 10th range linear single indicator 11th range linear single indicator 12th range linear single indicator 13th range

Measurement Range:

-20.0/+56.0 decibels single indicator 1st range +0.0/+0.5 milliamperes, dc single indicator 2nd range +0.0/+50.0 milliamperes, dc single indicator 3rd range +0.0/+250.0 milliamperes, dc single indicator 4th range +0.0/+100000.0 ohms single indicator 5th range +0.0/+10.0 volts

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Hand-held

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0